SAFETY DATA SHEET

EZ SHEEN

Infosafe No.: LQDGI
ISSUED Date : 03/09/2026
ISSUED by: OMIKRON AUTO DETAILING PRODUCTS PTY LTD

Section 1 - Identification

Product Identifier
EZ SHEEN

Product Code
EZSHE

Company Name
OMIKRON AUTO DETAILING PRODUCTS PTY LTD (ABN 51648142134)

Address
12 McPherson Road Smeaton Grange
NSW 2567 Australia

Telephone/Fax Number
Tel: 02 98245966

Emergency Phone Number
Poisons Information Centre: 13 11 26 (24 hours)

For Ambulance, Police or Fire Services: Call Triple Zero (000)

Recommended use of the chemical and restrictions on use
Non-silicone tyre and rubber dressing.

Other Names

Name	Product Code
EZ SHEEN SILICONE FREE TYRE SHINE 1L	EZSHE1T
EZ SHEEN SILICONE FREE TYRE SHINE 5.1L	EZSHE5
EZ SHEEN SILICONE FREE TYRE SHINE 20L	EZSHE20
EZ SHEEN SILICONE FREE TYRE SHINE 200L	EZSHE200

Illicit Drug Precursors
This product contains a Category III: Illicit Drug Reagent/Essential Chemical in the Code of Practice for Supply Diversion into Illicit Drug Manufacture.

Section 2 - Hazard(s) Identification

GHS classification of the substance/mixture
Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.
Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Flammable liquids: Category 3
Eye damage/irritation: Category 2A

Signal Word (s)
WARNING

Hazard Statement (s)
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.

Pictogram (s)
Exclamation mark,Flame



Precautionary Statement – Prevention
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Precautionary Statement – Response
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use carbon dioxide, dry chemical, foam, water mist or water spray to extinguish.

Precautionary Statement – Storage
P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary Statement – Disposal
P501 Dispose of contents/container to an approved waste disposal plant.

Other Information
This product contains an Ototoxic substance. Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

Section 3 - Composition and Information on Ingredients

Ingredients

Name	CAS	Proportion
Ethanol	64-17-5	10-<30 %
Glycerin	56-81-5	10-<30 %
Ingredients determined not to be hazardous, including water	-	Balance

Section 4 - First Aid Measures

Inhalation
If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

Ingestion
Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.

Skin
Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.

Eye
If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities
Eyewash, safety shower and normal washroom facilities.

Advice to Doctor
Treat symptomatically.

Other Information
For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

Section 5 - Firefighting Measures

Suitable Extinguishing Media
Carbon dioxide, dry chemical, foam, water mist or water spray.

Hazards from Combustion Products
Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific hazards arising from the chemical
Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code
•3Y

Decomposition Temperature
Not available

Precautions in connection with Fire
Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

Section 6 - Accidental Release Measures

Emergency Procedures
Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. As a water based product, if spilt on electrical equipment the product will cause short-circuits. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

Section 7 - Handling and Storage

Precautions for Safe Handling
Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with local exhaust ventilation, away from sparks, flames and other ignition sources. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers tightly closed. Take precautionary measures against static discharges. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Conditions for safe storage, including any incompatibilities
Store in a cool, dry, well-ventilated area away from sources of ignition, foodstuffs, clothing and incompatible materials such as oxidising agents. Protect from freezing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

Section 8 - Exposure Controls and Personal Protection

Occupational exposure limit values
No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Ethanol
TWA: 1000 ppm, 1880 mg/m³

Glycerin
TWA: 10 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Source: Safe Work Australia - Workplace exposure standards for airborne contaminants. (Repealed 1st December 2026)

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Ethanol
TWA: 200 ppm, 380 mg/m³
STEL: 800 ppm, 1500 mg/m³
NOTE: OTO

Glycerin
TWA: 10 mg/m³

TWA (Time Weighted Average): The TWA is the maximum average concentration of an airborne contaminant calculated for an eight-hour working day, based on a 5-day working week (40 hours). A worker must not be exposed to a level above the TWA over the course of an 8-hour working day.

STEL (Short Term Exposure Limit): A STEL is the time weighted average maximum concentration of an airborne contaminant calculated over a 15 minute period. It is intended to protect most workers from the acute effects of exposure.

'OTO' Notice: Ototoxic. Exposure can increase the risk of hearing loss. Hearing loss is more likely to occur if a worker is exposed to both noise and ototoxic substances than if exposed to just noise or the ototoxic substance alone. Refer to the Model Code of Practice: Managing noise and preventing hearing loss at work.

Source: Safe Work Australia - Workplace exposure limits for airborne contaminants. (In force from December 1st 2026)

Biological Monitoring
No biological limits allocated.

Control Banding
Not available

Engineering Controls
This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

Respiratory Protection
If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye and Face Protection
Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

Hand Protection
Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Thermal Hazards
No further relevant information available.

Body Protection
Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Section 9 - Physical and Chemical Properties

Properties	Description	Properties	Description
Form	Liquid	**Appearance**	Clear colourless liquid
Colour	Clear colourless	**Odour**	Mild floral fragrance
Melting/Freezing Point	Not available	**Boiling Point**	Not available
Decomposition Temperature	Not available	**Solubility in Water**	Soluble
Specific Gravity	Not available	**pH**	Not available
Vapour Pressure	Not available	**Relative Vapour Density (Air=1)**	Not available
Evaporation Rate	Not available	**Odour Threshold**	Not available
Viscosity	Not available	**Volatile Component**	Not available
Partition Coefficient: n-octanol/water (log value)	Not available	**Flash Point**	40 °C
Flammability	Flammable liquid	**Auto-Ignition Temperature**	Not available
Explosion Limit - Upper	Not available	**Explosion Limit - Lower**	Not available
Explosion Properties	Not available	**Oxidising Properties**	Not available
Particle Characteristics	Not available		

Section 10 - Stability and Reactivity

Reactivity
Reacts with incompatible materials.

Chemical Stability
Stable under normal conditions of storage and handling.

Possibility of hazardous reactions
Reacts with incompatible materials.

Conditions to Avoid
Heat, open flames and other sources of ignition.

Incompatible Materials
Strong oxidising agents.

Hazardous Decomposition Products
Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Hazardous Polymerization
Not available

Section 11 - Toxicological Information

Toxicology Information
No toxicity data available for this material.

Ingestion
Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

Inhalation
Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

Skin
May be irritating to skin. The symptoms may include redness, itching and swelling.

Eye
Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Respiratory Sensitisation
Not expected to be a respiratory sensitiser.

Skin Sensitisation
Not expected to be a skin sensitiser.

Germ Cell Mutagenicity
Not considered to be a mutagenic hazard.

Carcinogenicity
Not considered to be a carcinogenic hazard.

Reproductive Toxicity
Not considered to be toxic to reproduction.

STOT - Single Exposure
Not expected to cause toxicity to a specific target organ.

STOT - Repeated Exposure
Not expected to cause toxicity to a specific target organ.

Aspiration Hazard
Not expected to be an aspiration hazard.

Other Information
This product contains an Ototoxic substance. Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

Section 12 - Ecological Information

Ecotoxicity
No ecological data available for this material.

Persistence and degradability
Not available

Mobility
Not available

Bioaccumulative Potential
Not available

Other Adverse Effects
Not available

Environmental Protection
Prevent this material entering waterways, drains and sewers.

Hazardous to the Ozone Layer
This product is not expected to deplete the ozone layer.

Section 13 - Disposal Considerations

Disposal Considerations
Dispose of waste according to applicable local and national regulations. To minimise personal exposure, refer to Section 8 - Exposure Controls and Personal Protection.

Section 14 - Transport Information

Transport Information
This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)
Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:
- Class 1: Explosives
- Division 2.1: Flammable Gases.
(Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L)
- Division 2.3: Toxic Gases
- Division 4.2: Spontaneously Combustible Substances
- Division 5.1: Oxidising substances
- Division 5.2: Organic Peroxides
- Class 6: Toxic or Infectious Substances
(where the flammable liquid is nitromethane)
- Class 7: Radioactive materials unless specifically exempted

UN Number
1993

Proper Shipping Name
FLAMMABLE LIQUID, N.O.S.(Contains Ethanol)

Transport Hazard Class
3

Packing Group
III

Hazchem Code
•3Y

Special Precautions for User
Not available

IATA UN Number
1993

IATA Proper Shipping Name
Flammable liquid, n.o.s. (Contains Ethanol)

IATA/ICAO Symbol
Flamm. liquid

IATA Transport Hazard Class
3

IATA Packing Group
III

IMDG UN Number
1993

IMDG Proper Shipping Name
FLAMMABLE LIQUID, N.O.S. (Contains Ethanol)

IMDG Transport Hazard Class
3

IMDG Packing Group
III

IMDG EMS
F-E, S-E

IMDG Marine pollutant
No

Transport in Bulk
Not available

Section 15 - Regulatory Information

Regulatory Information
Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) including Work, Health and Safety Regulations, Australia.

Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule
Not Scheduled

Montreal Protocol
Not listed

Stockholm Convention
Not listed

Rotterdam Convention
Not listed

International Convention for the Prevention of Pollution from Ships (MARPOL)
Not available

Agricultural and Veterinary Chemicals Act 1994
Not available

Basel Convention
Not listed

Section 16 - Any Other Relevant Information

Date of Preparation
SDS Created: September 2026.

Version Number
1.0

Literature References
Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
Standard for the Uniform Scheduling of Medicines and Poisons.
Australian Code for the Transport of Dangerous Goods by Road & Rail.
Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
Code of Practice for Supply Diversion into Illicit Drug Manufacture.
National Code of Practice for Chemicals of Security Concern.
Agricultural Compounds and Veterinary Chemicals Act.
International Agency for Research on Cancer (IARC) Monographs.
Montreal Protocol on Substances that Deplete the Ozone Layer.
Stockholm Convention on Persistent Organic Pollutants (POPs).
Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade.
Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and Their Disposal.
International Air Transport Association (IATA) Dangerous Goods Regulations.
International Maritime Dangerous Goods (IMDG) Code.
Workplace exposure standards for airborne contaminants.
Workplace exposure limits for airborne contaminants.
Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).
Globally Harmonised System of Classification and Labelling of Chemicals (7th revised edition).
Code of Practice: Managing Noise and Preventing Hearing Loss at Work.

END OF SDS

© Copyright Chemical Safety International Pty Ltd
Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.
Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.
The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.
Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.